

BSD 00, 000, 000 0000

Abstract

00000000 00000000 0000 "00000000 00000000" 0000 0000 00000000 00 0000 0000 0000 000000 00000000'00 00000000 00000000 00000000 0000 0000 00000000 00000000 00000000 00000000 00000000 00000000 0000 00 00000000 00000000 000000000000 0000 000000 00000000 00.0% 0000000000 00000000 0000 00 0000000000 00 00.0% 0000000000 00000000 00 BSD 00000000 00000000 0000000000; 0000000000 00000000 0000000000000000 0000000, 00000, [Yahoo!](#) BSD 00000000 00000000 0000 000000 00000000 0000000000 [FTP](#) 00000000 [ftp.cdrom.com](#) BSD 00000000 0000 0000000000 000000 0.0 0000000000 0000 00000 0000000 0000 00000000 BSD'0 000000 00 00000000 0000, 0000 0000 00000000 0000 BSD 0000 0000000000 00000000 00000 0000000000

BSD'0 00000000 00000000 000000 00 0000 000000 0000 ? 00 0000000000 0000 00000 0000 00000 0000000000000000 00 000000 000000000000

00 0000000000 BSD 0 00000000000 00 0000000000000000 000000 00000000 0000 00000

Table of Contents

- 1. BSD 00 ? 1
- 2. 000 0000000!!! 0000 0000 00 ? 2
- 3. BSD 000 00000000 00 ? 3
- 4. BSD 0000 0000000000 3

1. BSD 00 ?

BSD 0000 00 *Berkley Software Distribution* 0 000000000000 BSD 0000 0000000000000000 00000000000000, 00000000 0000 0000000000 000000000000 0000000 0000 [AT&T](#)'0 000000000000 0000000000 0000000000 0000000000 0000 00000000 0000 0000000000 [4.4BSD-Lite](#) 0000 00000000 00 0000000000 00000000 0000 0000 00000000 0000000000 0000000000 0000 0000000000 0000 00000 0000000000 0000000000 00000000 00000000 00000000 00000000 00000000 00000000 0000, 0000 000000 000000000000 00 00000 (GNU) 00000000000 0000000000000000 0000 BSD 0000000000 0000000000 00000000 00000000 0000 0000

BSD 00000000

0000 00000000 0000000000 000000 0000 0 000000 000000 0000 0000 00000000 0000000 000000 0000000000 000000 0000000000 0000000000 000000

00000000 00000000 00, 00000000000 00000000 0000 0000 00000000000 000000, 00000000 BSD 00000000000 00000000 00000000 0000 00000000000000 000000 0000000000000000 0000 0000000000 0000000000 0000

C 0000000000

0000 00 0000000000 0000000000 [API](#) 00000000 0000 0000000000

BSD C 000000000000 0000000000 0000000000 0000000000 0000, 00000 (GNU) 000000000000 0000 00000 0000

4. 通常情況下，CVS 是 BSD 的代碼庫。但對於 FreeBSD 來說，CVS 是代碼庫，而 BSD 是代碼庫。通常情況下，CVS 是代碼庫，而 BSD 是代碼庫。

通常情況下，BSD 是代碼庫。通常情況下，BSD 是代碼庫。通常情況下，BSD 是代碼庫。通常情況下，BSD 是代碼庫。通常情況下，BSD 是代碼庫。

1. 通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。

2. 通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。

3. RELEASE 通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。

4.3. BSD 的代碼庫

通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。

通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。

- FreeBSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。
- NetBSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。
- OpenBSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。通常情況下，CVS 是 BSD 的代碼庫。

BSD license and other licenses

BSD license and other licenses are used in BSD/OS and Mac OS X

- 4.4 BSD license and other licenses are used in BSD/OS and Mac OS X, and FreeBSD's BSD/OS license is also used
- BSD license and other licenses are used in Mac OS X and FreeBSD's BSD license is also used

4.4. BSD and GNU licenses

BSD license and GNU General Public License (GPL) are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.

4.5. BSD license and other licenses

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.

4.6. BSD license and other licenses

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.

- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.
- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.
- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.
- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.

- 0000000000 00000000 BSD'00 0000000 000000 0000 00000000 000000 0000 00 0000 0000000000 0000000000 0000000000 00000000 00000000 BSD'0 0000000000 00000000 0000000000 000000 0000000

4.7. BSD 000000000000 000000 0 0000000000000

BSDi 00000000 BSD/OS 000000000000 00000 00000 00000000 0000000000 00000 FreeBSD 0000000000 00000 00000000 0000000000

00000000 FreeBSD, NetBSD 0 OpenBSD'0 0000000000 0000000000 000000 0000000 00000 0000000000000 0000000000 0000000000000000 00000 00000 0000000 00000